



# MAZDA Dexelia GENUINE 10W-40

## Applications

- |  |   |
|--|---|
| <p>The most severe routes</p> <p>All times of year, even in the coldest conditions</p> | <ul style="list-style-type: none"> <li>■ Recommended for all(*) petrol engines (multi-valve and turbo types, with or without catalytic converter) and all diesel engines, turbo-charged or naturally aspirated in cars and light vans.</li> <li>(*) For Renesis engines, Dexelia Ultra 5W30 is highly recommended</li> <li>■ For all types of service (urban, highway and motorway driving) particularly in the most extreme conditions.</li> <li>■ Suitable for all driving styles.</li> </ul> |
|--|---|

## Advantages to the client

- |   |  |
|---|--|
| <p>Advanced technology</p> <p>Protecting the environment</p> <p>Very advanced performance</p> | <ul style="list-style-type: none"> <li>■ Stability of its multigrade characteristics during the whole service period.</li> <li>■ Exceptional thermal stability.</li> <li>■ Detergent and dispersing, anti-foam, anti-oxidation and anti-corrosion abilities, meeting the requirements of the above mentioned specifications.</li> <li>■ Formulated to counteract "Black Sludge".</li> <li>■ Reinforced anti-wear properties thus meeting the severest requirements of the manufacturers.</li> <li>■ Excellent cold flow properties imparting easy starting even at low temperatures.</li> <li>■ Immediate lubrication of all engine parts at low starting temperatures, reducing wear and resulting in an extended engine life.</li> </ul> |
|---|--|

**TOTAL LUBRIFIANTS**  
16, rue de la République  
92800 PUTEAUX  
1/2

**Mazda Dexelia GENUINE 10W-40**  
**March 07**  
**MGP 07 / 03**



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.  
A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.



## Specifications

ACEA 02: A3/B3  
API: SL/CF

- Exceeds the latest and most stringent requirements of the following specifications:
  - ACEA – 02 : A3/B3
  - API SL/CF

## Characteristics

Density at 15 °C	0,871
Kinematic viscosity at 40 °C	95,35 mm <sup>2</sup> /s (cSt)
Kinematic viscosity at 100 °C	14,84 mm <sup>2</sup> /s (cSt)
Dynamic viscosity at -25 °C	6 111 mPa.s (cP)
Viscosity Index	163
Pour point	< -33°C
Flash point (C.O.C.)	230°C
T.B.N	11,5 mg KOH/g

*(Typical values given as an example)*

**TOTAL LUBRIFIANTS**  
16, rue de la République  
92800 PUTEAUX  
2/2

**Mazda Dexelia GENUINE 10W-40**  
**March 07**  
**MGP 07 / 03**



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.  
A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.